



**nev L4S.6**



60 VOLT WITH AC SYSTEM

AGM OR LITHIUM BATTERIES

155/65 R13 STEEL RIMS  
WITH WHEEL COVERS

LED LIGHTS WITH DRL  
FUNCTION

HYDRAULIC BRAKES ON 4  
WHEELS + HANDBRAKE

R.01 - SET.24

**ITALCAR INDUSTRIAL SRL** | Via Bruino, 36 | 10040 Rivalta di Torino (TO)  
Tel. +39 011 9040225 | Fax +39 011 9032986 | [info@italcar.com](mailto:info@italcar.com) | [www.italcar.com](http://www.italcar.com)



## nev L4S.6



ITALCAR is an Italian brand

<b>places:</b>	4
<b>batteries:</b>	AGM or LITHIUM
<b>motor:</b>	AC – 60V
<b>controller:</b>	AC – 450°
<b>transmission:</b>	rear axle, ratio 12,49:1
<b>steering:</b>	self compensating single reduction rack and pignon
<b>performances:</b>	
<b>max speed:</b>	45 km/h
<b>range:</b>	80km (AGM) – 110km (LITHIUM)
<b>max hill climbing ability:</b>	20% (then 11°)
<b>dimensions:</b>	
<b>overall (LxWxH)</b>	2870mm x 1400mm x 1750mm
<b>ground clearance (empty):</b>	145mm
<b>turning radius:</b>	5,6 mt
<b>chassis:</b>	galvanized steel frame and powder coated
<b>body:</b>	PP impregnated and painted
<b>suspensions:</b>	
<b>front</b>	independent suspensions
<b>rear</b>	leaf springs with hydraulic shock absorbers
<b>brakes:</b>	automotive types, double hydraulic circuit on four wheel with hand brake
<b>front</b>	disc
<b>rear</b>	disc
<b>tyres:</b>	155 / 65 – 13
<b>reccomended pressure:</b>	2,5 bar (25kPa)
<b>battery charger:</b>	included
<b>basic configuration:</b>	roll-bar with 3-point safety belts, laminated glass windscreen, front and rear lights and direction indicators, side and central mirrors, glove compartment, radio, USB charging slot, air conditioning

**\* average autonomy measured on a flat road @ constant speed of 20km/h**

*all above specification were correct at the time of the publishing and are indicatives and not binding.  
ITALCAR INDUSTRIAL Srl maintains the right to bring any changes without notice*

*seguici su - follow us on*



*clicca mi piace - like us on*

